


COARSE BARRIER PRIMER (ready for use)

Quartz-filled primer with blocking effect; prevents from nicotine stains, soot, grease and oil stains on various surfaces. For indoor use.

Consumption
150 – 300 g / m², depending on surface condition



Article no.	kg/package	colour	package/pallet
39408	6	white pigmented	60
39409	15	white pigmented	30

KAST Coarse Barrier Primer

is a primer material with high adhesion and high insulating effect for plasterboard and chipboard as well as for the binding of nicotine stains, dry water stains, soot, oil and grease stains before subsequent structural coatings in interior areas. Creates non-slip surfaces.


Substrate

load-bearing, dry, free of dust, grease, oil, calcareous deposits, efflorescence and release agents

Storage

Tightly closed, dry, frost-free; protect from heat and direct sunlight
Shelf life 12 months in unopened original packaging


Also available as concentrate for 10-20% water addition



Dr. Günther Kast GmbH & Co.
Technische Gewebe
Spezial-Fasererzeugnisse KG
Abt-Reubi-Straße 6
87527 Sonthofen / Germany

Tel: +49 8321 6641-0
Fax: +49 8321 6641-66

info@kast.de
www.kast.de



Dr. Günther Kast GmbH & Co.
Technische Gewebe Spezial-Fasererzeugnisse KG



CONSTRUCTION PRIMERS

DEEP PRIMER LF

STABILIZING PRIMER

RENDER PRIMER

CONCRETE BONDING AGENT

COARSE BARRIER PRIMER

DEEP PRIMER LF (ready for use)

Special primer for highly absorbent and sanding surfaces.
For interior and exterior use.

Solvent- and plasticizer-free, tack-free

Consumption

150 – 200 ml / m², depending on surface condition



Article no.	liter/container	colour	containers/pallet
39399	5	milky white	96
39400	10	milky white	60

KAST deep primer LF

is a permeable, alkali-resistant, ready-to-use, milky white, low-odour synthetic resin-based primer. It consolidates friable and sanding plaster and concrete surfaces as well as all other mineral surfaces and creates load-bearing or evenly absorbing substrates for subsequent plastering, painting and tiling work. Comes with a very high penetration capacity, surface hardening and absorbency regulating effect, reduces burning and thus shrinkage cracks, binds dust and dries colourless.

Substrate

load-bearing, dry, free from dust, grease, oil, sintered layers, efflorescence and separating agents

Storage

Tightly closed, dry, frost-free; protect from heat and direct sunlight
Shelf life 12 months in unopened original packaging



RENDER PRIMER (ready for use)

Quartz-filled and permeable primer for decorative plasters on mineral surfaces, regulates absorbency, improves adhesion. For interior and exterior use.

Solvent- and plasticizer-free

Consumption

150 – 300 g / m², depending on surface condition



Article no.	kg/package	colour	package/pallet
39403	6	white pigmented	60
39405	20	white pigmented	24

KAST Render primer

is used to improve adhesion before final coatings of finishing plasters. It reduces or equalises and regulates the absorption behaviour of the plaster base and improves the bond with the corresponding finishing plasters.

Substrate

load-bearing, dry, free of dust, grease, oil, sintered layers, efflorescence and separating agents

Storage

Tightly closed, dry, frost-free; protect from heat and direct sunlight
Shelf life 12 months in unopened original packaging




STABILIZING PRIMER (ready for use)

Special primer for highly or differently absorbent surfaces.
For interior and exterior use.

Solvent- and plasticizer-free

Consumption

100 – 150 ml / m², depending on surface condition



Article no.	liter/container	colour	containers/pallet
39401	5	ocher pigmented	60
39402	15	ocher pigmented	24

KAST Stabilizing primer

is a solvent-free primer material. It is used to prevent the „burning“ of plaster on strongly or differently absorbing plaster surfaces such as gas concrete, lightweight bricks, hollow perforated bricks as well as mixed masonry and strongly absorbing jointing mortars as a plaster bonding bridge according to DIN V 18550 for gypsum plaster, hand plaster, bonding binder and thin plaster.

Substrate

load-bearing, dry, free of dust, grease, oil, sintered layers, efflorescence and release agents

Storage

Tightly closed, dry, frost-free; protect from heat and direct sunlight
Shelf life 12 months in unopened original packaging

Also available as concentrate for 10-20% water addition




CONCRETE BONDING AGENT (ready for use)

Quick-drying bonding agent for plasters and binders, especially on concrete and smooth surfaces. For interior and exterior use. Weather resistant.

Solvent- and plasticizer-free

Consumption

200 – 350 g / m², depending on surface condition



Article no.	kg/package	colour	package/pallet
39406	6	red pigmented	60
39407	20	red pigmented	24

KAST Concrete bonding agent

improves the mechanical adhesion of base, cement and lime-cement plasters, machine plaster, finished plaster gypsum and other dense, non-absorbent surfaces as a plaster bonding bridge according to DIN V 18550. Creates non-slip surfaces, stabilizes render and prevents shrinkage cracks, regulates absorbency, is open to diffusion and alkali-resistant.

Substrate

load-bearing, dry, free of dust, grease, oil, sintered layers, efflorescence and release agents

Storage

Tightly closed, dry, frost-free; protect from heat and direct sunlight
Shelf life 12 months in unopened original packaging

Also available as concentrate for 10-20% water addition

